




Website: www.felixmachines.com





Contact Us: Kellye Just
971 270-0131
assist@felixmachines.com



Cylindrical Cell Assembly Equipment p1

| Picture | Model | Specification | Felix Machines Price | Delivery Time |
|---|------------------|---|----------------------|---------------|
|  | MRX-FT300 | Electrode slitting machine Cutting width : 20- 300mm Thickness of the cutting electrode : 80-300um battery electrode Burrs ≤ 25um Dia of cutting blade : 85mm Cutting speed : Max 4m/min adjustable Dimension : L850 x W920 x H400mm Weight : ≈ 100kg | US \$11,500 | 25 days |
|  | MRX-JR90 | Manual winding machine Power supply: 220V/50Hz Power : 40W Rotating speed: 0~170r/min, adjustable Applicable cylindrical battery core: dia < Φ30 Dimension: L360mm*310mm*280mm Weight: 25Kg | US \$2,200 | 25 days |
|  | MRX-JZ300 | Electrolyte diffusion chamber The chamber is made of aluminum that is anti- corrosion, and structure is stable. Diffusion time can be regulated from 0 to 9999s. Vacuum degree can reach -90KPa(vacuum pump should be self-supplied by the buyer). Power supply: 220V/50Hz Power: 50W Compressed air source: 0.5~0.7Mpa Working temperature: -20~40 °C Dimension inside the chamber: L355mm*W256mm*H325mm Dimension of the equipment Moving part of executive chamber: about L510mm*W300mm*H820mm Control part: about L450mm*W370mm*H260mm Weight: ~ 40KG | US \$4,700 | 25 days |

Cylindrical Cell Assembly Equipment p2

| Picture | Model | Specification | Felix Machines Price | Delivery Time |
|---|-------------------|--|---|---------------|
|  | MRX-DH650 | Spot welding machine Max output power: 10KVA Welding current: 00~99 Power: AC220V±10% 50~60Hz Input air pressure: 0.3~0.7MPa Application: applicable for many welding pieces of 0.03mm~0.25mm Whole equipment weight: 45Kg Dimension: L400×W560×H400mm | US \$2,700 | 14 days |
|  | MRX-GC650 | Cylinder cell grooving machine Regulating range of grooving depth: 1.2-2mm adjustable Grooving speed: ~300r/S(adjustable) Grooving width: 1.1-1.5mm(depends on the thickness of grooving cutter) Accuracy: ±0.1mm Capacity: 6~8个/min(demands on familiarity) Power supply: 220v/50HZ 140W Compressed air: 0.5~0.7MPa Component material: high-strengthen chrome steel, and never rusts for the surface is treated through environmental electroplating and painting | US \$5,600 with 18650 grooving die included | 14 days |
|  | MRX-SF650 | Cylinder cell crimping machine Standard equipped with a set of 18650 cylindrical battery sealing mould.(Other cylindrical battery sealing mould is optional) Sealing pressure: pressure gauge at 55-800kg/cm2 The mould material is imported from Japan. Service life of mould is more than 300,000 times, there is no scratches on the appearance after sealed. Component material: high-strengthen chrome steel with the surface treated through environmental electroplating and painting and never rusts Dimension: 235mm X 190mm X 360mm Weight: 40kg | US \$3,700 with crimping die included | 14 days |
|  | MRX-DH1000 | Ultrasonic metal welding machine 1000W Working volt :AC220V / 50Hz Working compressed air source : 0.5 -0.7Mpa. Working frequency : 40KHz Input power : 0 - 1000VA Welding time : 0-1s Controller dimension : L360xW480x H200mm Welder dimesion : L300xW460x H270mm | US \$13,600 | 25 days |